

ULTRA Series

UL-759A (VBS-HDIP-759A)

Just Add
Power
AV over IP Solutions



View 4 Sources on 1 Display

The Ultra Series 759A Video Tiler gives any Just Add Power system the ability to mix four video sources from any Encoder (Transmitter) and combine those into a new, unique, compiled video source that can be viewed by any Decoder (Receiver) in the matrix.

Tile four (or more) HDMI sources on a single display in a variety of viewing modes: single-screen, video wall, or tiled video at the same time. Like any standalone Decoder (Receiver), the Decoders (Receivers) in the 759A Video Tiler can watch any source in the system and can then be shown on any display in the system. Multiple video tilers can be combined to add even more sources on a single display.

Features


Combine Video Tilers	<p>Stack two or more tilers together to break the 4-tile limit. There is no limit to the number of tiles</p> <p>A single tiler can show up to 4 sources on any receiver. Two tilers can show up to 7 sources on any receiver. Continuing this pattern: each additional tiler adds 3 video sources to any screen</p>	Image Pull	<p>Provides a more powerful user experience giving the control system the capability of displaying a preview image inside the user interface</p>
Custom Layouts	<p>Create and build custom layout sizing and placement</p>	Integrated Endpoint Control	<p>Control endpoints with IR</p>
HDMI	<p>Local HDMI Out</p>	Resolution	<p>Mix any resolution source</p>
		Scalability	<p>Fully compatible with 4K systems Limited feature set with 1080p systems</p>

ULTRA Series

UL-759A (VBS-HDIP-759A)


Just Add
Power
AV over IP Solutions

Front of Device:



All measurements in millimeters (mm)

Back of Device:



All measurements in millimeters (mm)

Specifications

Bandwidth	180-500 Mbps	Operating Temp	0-60 °C / 32-140 °F
Compliance	HDCP 2.2 & RoHS/FCC/CE	Ports	Gigabit Ethernet (x5) HDMI Out 3.5mm Stereo Out
Dimensions & Weight	429 x 44.5 x 250mm 17" x 1.75" x 9.8" inch (19-inch rack, 1 RU) 2.9 kg / 6.4 lb	Power Supply (included)	IEC 60320 C13/C14 50W AC Power
Encryption	AES-128 Encryption	Supported Audio & Video	Audio: Stereo Audio . Audio Volume and Delay. Video: Up to 4096x2160