

PT-MA-HD44M




Features

- ▶ Matrix switching of 4 HDMI signals to 4 HDMI outputs
- ▶ Supports 18Gbps for resolutions up to 4K UltraHD 60Hz
- ▶ Analog and digital audio de-embedding, front panel display
- ▶ Control via buttons, web-GUI, CEC, RS232 and IR
- ▶ Ultra compact enclosure (1/2 19") with screwable power supply

Technical Data

PT-MA-HD44M

Input / Output	
Inputs	4x HDMI-A
Outputs	4x HDMI-A, 4x Stereo (3-pin Phoenix), 4x S/PDIF (Coax)
Control	
Control Ports	1x IR Eye (3.5mm Jack), 1x RS232 (3-pin Phoenix), 1x IP (RJ45)
Push-Buttons	4x Input, 4x Output, 1x "Menu", 1x "Preset", 1x "Lock", 3x Control ("Up", "Down", "Enter")
Remote Control	Standby, Mute, Key Lock, Inputs / Outputs with Various Functions, Mirroring, Menu Navigation
LCD Display	GUI for Control via Frontpanel Buttons or Remote Control incl. Video, Audio, EDID, Preset and Setup Settings
Default IP	192.168.1.168
Other	1x IR-Eye (Integrated), 1x IR Extension Cable, incl. 1x IR Remote Control
Technical Data	
Max. Resolution	4K / UltraHD @60Hz (4:4:4)
Bandwidth	18 Gbps
HDMI / HDCP Standard	HDMI 2.0 / HDCP 2.2
Audio Formats	PCM 2.0, LPCM 5.1 / 7.1, Dolby True HD / DTS-HD Master Audio
General	
Product Dimensions	216.2 x 128.5 x 34 mm
Product Weight	470g
Housing Material	Steel
Colour	Black
Operation Temperature	0 ~ 40 °C
Relative Humidity	5% ~ 90%
Power Supply	DC 12V / 2A, Screwable Plug
Energy Consumption	Max. 14W
Compliance	CE, RoHS, REACH, PAP20



FRONT



BACK

Product Overview

Art.-No.	Colour	EAN
PT-MA-HD44M	black	4251364734759

PureLink GmbH | Von-Liebig-Str. 10 | 48432 Rheine | Germany | ☎ +49 5971 800 299-0 | 📠 +49 5971 800 299-99 | ✉ info@purelink.de

We regularly expand our product range. We will be happy to provide information on updates in this regard upon request. All information is subject to confirmation and non-binding. Technical changes, printing errors and mistakes excepted. The illustrations used in these documents may differ from the delivered product.

