# iSeries IS2400 to IS2611 USB 3.2 Cables

## Yesterday a Data Cable, Today a Video Cable, Tomorrow... - Who Knows?!

USB-C has the potential to replace every popular connector you know. Using the DisplayPort Alt-Mode, the functions of all interfaces can automatically adapt to USB-C, enabling data, AV and power transmission over one single standard. The iSeries USB 3.2 connection cables were designed to take full advantage of this flexibility to meet any modern connectivity challenge. The cables allow you to power devices with up

to 100W and a variable voltage, using the USB Power Delivery standard. They also provide a data transfer rate up to 10Gbps, making them suitable for a direct AV connection to digital displays with a variety of video formats. We promise nothing less than the best possible product quality, verified by the strictest PureLink testing standards.



# USB 3.2 Cable Range

With the iSeries IS2400 to IS2611, PureLink offers a comprehensive range of USB 3.2 connection cables with USB-C or USB-A connectors on both sides or as USB-C to USB-A version.

# Large Selection

Colour selection white / black in lengths between 0.50 and 2.00 meters. All versions are available as 5Gbps version according to USB 3.2 Gen1 or as 10Gbps version according to USB 3.2 Gen2 standard.

# **One Single Standard**

Enable your devices to transfer AV streams, power incl. USB Power Delivery, control signals as well as general data signals via the USB-C Alt-Mode.

## **High Quality Finish**

Precisely fitting, high-quality connectors with gold-plated contacts round off the state-of-the-art electronics, thus enabling the multifunctional signal transmission.

## Future-Proof Cable Technology

With high-purity inner copper conductors and a triple shielding structure, the transmission quality is permanently verified. Connect and forget.

#### **Retail Optimized Packaging**

The high-quality, multilingual packaging stands out at every point of sale due to its attractive design, while being optimized for warehousing and perfect product protection.



Product Overview IS2400 to IS2611 USB 3.2 Cables

	Parent	Art. No.	Length	Connector	Description	Net MSR
	IS2400	IS2400-005	0.50m	USB-A ↔ USB-A	USB 3.2 (Gen1) cable with 5Gbps,	5.80 4
CT .		IS2400-010	1.00m		both sides with USB-A male connectors,	6.29
		IS2400-015	1.50m		3A/5V/15W max. power output	6.64
C.		IS2400-020	2.00m		white	7.13
	IS2401	IS2401-005	0.50m	$USB-A \leftrightarrow USB-A$	USB 3.2 (Gen1) cable with 5Gbps,	5.80
The second se		IS2401-010	1.00m		both sides with USB-A male connectors,	6.29
		IS2401-015	1.50m		3A/5V/15W max. power output	6.64
<b>N</b>		IS2401-020	2.00m		black	7.13
	IS2410	IS2410-005	0.50m	USB-A ↔ USB-A	USB 3.2 (Gen2) cable with 10Gbps,	6.29
GT -		IS2410-010	1.00m		both sides with USB-A male connectors,	6.64
					3A/5V/15W max. power output	
100 C					white	
	IS2411	IS2411-005	0.50m	USB-A ↔ USB-A	USB 3.2 (Gen2) cable with 10Gbps,	6.29
	192411	IS2411-005	1.00m		both sides with USB-A male connectors,	6.64
		152411-010	1.00111		3A/5V/15W max. power output	0.04
					black	
	IS2500	IS2500-005	0.50m	USB-C ↔ USB-C	USB 3.2 (Gen1) cable with 5Gbps,	10.84
		IS2500-010	1.00m		both sides with USB-C male connectors, E-Marker,	11.68
A CA		IS2500-015	1.50m		USB PD with 3A/20V/60W, DP Alt-Mode	13.36
C.		IS2500-020	2.00m		white	14.20
		152500 020	2.0011		white	14.20
	IS2501	IS2501-005	0.50m	USB-C ↔ USB-C	USB 3.2 (Gen1) cable with 5Gbps,	10.84
		IS2501-010	1.00m		both sides with USB-C male connectors, E-Marker,	11.68
		IS2501-015	1.50m		USB PD with 3A/20V/60W, DP Alt-Mode	13.36
	>	IS2501-020	2.00m		black	14.20
	IS2510	IS2510-005	0.50m	USB-C ↔ USB-C	USB 3.2 (Gen2) cable with 10Gbps,	12.52
		IS2510-010	1.00m		both sides with USB-C male connectors, E-Marker,	13.36
1 Care		IS2510-015	1.50m		USB PD with 5A/20V/100W, DP Alt-Mode	14.20
Ch in		132310 013	1.5011		white	14.20
	IS2511	IS2511-005	0,50m	USB-C ↔ USB-C	USB 3.2 (Gen2) cable with 10Gbps,	12 52
	137211	IS2511-005		J-dcu ↔ J-dcu	both sides with USB-C male connectors, E-Marker,	12.52
		IS2511-010	1,00m			13.36
		IS2511-015	1,50m		USB PD with 5A/20V/100W, DP Alt-Mode	14.20

# **Product Overview**

IS2400 to IS2611 USB 3.2 Cables

F	Parent	Art. No.	Length	Connector	Description	Net MSRP
	S2600	IS2600-005	0.50m	USB-C ↔ USB-A	USB 3.2 (Gen1) cable with 5Gbps,	7.48€
17		IS2600-010	1.00m		USB-C male to USB-A male,	8.32€
		IS2600-015	1.50m		3A/5V/15W max. power output	9.16€
13 ×		IS2600-020	2.00m		white	10.00€
	S2601	IS2601-005	0.50m	USB-C ↔ USB-A	USB 3.2 (Gen1) cable with 5Gbps,	7.48€
11		IS2601-010	1.00m		USB-C male to USB-A male,	8.32€
		IS2601-015	1.50m		3A/5V/15W max. power output	9.16€
		IS2601-020	2.00m		black	10.00€
	S2610	IS2610-005	0.50m	USB-C ↔ USB-A	USB 3.2 (Gen2) cable with 10Gbps,	7.48€
17		IS2610-010	1.00m		USB-C male to USB-A male,	8.32€
					3A/5V/15W max. power output white	
	S2611	IS2611-005	0.50m	USB-C ↔ USB-A	USB 3.2 (Gen2) cable with 10Gbps,	7.48€
1		IS2611-010	1.00m		USB-C male to USB-A male,	8.32€
					3A/5V/15W max. power output	
					black	

#### Kontakt

PureLink GmbH Von-Liebig-Str. 10 48432 Rheine | Germany J +49 5971 800 299-0
B +49 5971 800 299-99
➡ info@purelink.de

All information is subject to confirmation and non-binding. Technical changes, printing errors and mistakes excepted. All data as of July 2021

