



Ultra Mobile Digital Projector for Brilliant Presentations

The Vivitek D556 digital projector is ready for current and future media applications. With connectivity options including HDMI v.1.4, the D556 is Direct 3D for entertainment, features a high brightness of 3000 ANSI Lumens and a 15,000:1 contrast ratio. The D556 is able to deliver sharp, vibrant pictures. The new high efficiency lamp that lasts up to 10,000 hours makes the D556 an economic projector to run.

Features

- Native SVGA (800 x 600) resolution
- Super bright at 3,000 ANSI Lumens for dazzling images
- 15,000:1 contrast ratio for amazing picture quality
- High-efficiency lamp that last up to 10,000 hours
- Direct 3D via HDMI
- Convenient top loading design for easy lamp replacement
- 5 segment color-wheel for improved color reproduction and automatic gain control
- Source filtering function to save time locating device signal source
- Keypad lock prevents accidental system adjustments
- Rapid on/off for quick start up and shut down
- Built-in 2 watt audio speaker
- Ultra mobile at a weight of 2.3kg

Product Pictures



Specifications	
Display Type	DLP® BrilliantColor™ Technology
Brightness	3000 ANSI Lumens
Native Resolution	SVGA (800 x 600)
Maximum Resolution	UXGA (1600 x 1200)@60Hz
Contrast Ratio	15000:1
Uniformity	95%
Lamp Life and Type	5,000/6,000/10,000 Hours (Std./Eco/Dyn.Eco Mode)
Throw Ratio	1.92-2.14:1
Image Size (Diagonal)	23" - 256"
Projection Distance	1 -10m (3.28ft – 32.8ft)
Projection Lens	F = 2.52 - 2.73, f = 21.8 - 24mm
Zoom Ratio	1.1x
Aspect Ratio	4:3 Native
Offset	128% ± 10%
Keystone Correction	Vertical ± 40° (±40 Step)
Horizontal Frequency	2D: 15,30 – 91.4kHz/3D: 101.6kHz
Vertical Scan Rate	24 - 30Hz, 47 – 120Hz
Speakers	2W (Mono)
3D Ready	Yes, Direct 3D via HDMI
Lens Shift Range	N/A
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In ,HDMI, S-Video, Composite Video, Audio-In (RCA), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Keypad Lock
Dimensions (W x D x H)	274.6x 212 x 100mm
Weight	2.3kg
Noise Level	35dB/32dB (Normal/Eco Mode)
Power Supply	AC 100-240V, 50/ 60Hz
Power Consumption	200W (Eco Mode), 240W (Normal Mode), <0.5W (Standby Mode)
Warranty	2-Year Warranty, 1-Year or 1,000h Lamp Warranty
Standard Accessories	AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit
Optional Accessories	Replacement Lamp, Remote w/ Laser Pointer
UPC	814964 338020

