



## Versatile Portable Projector with High Brightness

### FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 4000 ANSI lumens of brightness and 30,000:1 contrast ratio for clear, crisp and bright presentations
- 1080p (1920 x 1080) native resolution scalable up to a maximum WUXGA (1920 x 1200) resolution
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- 6 segment (RYGCWB) colour wheel for vivid colour reproduction.
- HDMI inputs for high definition content with the same high quality
- 3D Ready for for creating immersive, interactive, and visually stunning experiences across various applications.
- The USB-A power provides for seamless integration with multimedia devices.
- Audio ready with built-in 10 watt audio speaker, audio-in and audio-out ports
- Compact and lightweight at 2.6kg for easy portability



## From meeting room to presentations anywhere on the road

The DH380 is a native 1080p digital projector from Vivitek. It features DLP® and BrilliantColor™ technologies to display distinct, vibrant images in a widescreen format. The Vivitek DH380p features numerous connectivity options including two HDMI v1.4 ports, a brightness level of 4000 ANSI Lumens and a 30,000:1 contrast ratio. With its light weight and compact for easy installation that will fit any budget.



## DH380 SPECIFICATIONS

Image	<b>Display Type</b>	Single chip DLP® Technology by Texas Instruments
	<b>Brightness</b>	4000 ANSI Lumens
	<b>Native Resolution</b>	1080p (1920 x 1080)
	<b>Max. Supported Resolution</b>	WUXGA (1920 x1200) @60Hz
	<b>Contrast Ratio</b>	30,000:1
	<b>Native Aspect Ratio</b>	16:9
	<b>Keystone Correction</b>	Vertical: +/-30°
Optical	<b>Throw Ratio</b>	1.48~1.62 : 1
	<b>Image Size (Diagonal)</b>	27.88"- 305.21"
	<b>Projection Distance</b>	1m -9.3m
	<b>Projection Lens</b>	F=2.47 - 2.66, f=20.4 - 24.48mm
	<b>Zoom Ratio</b>	1.1x
	<b>Offset</b>	116% ±5%
Features	<b>Features</b>	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Connectivity	<b>I/O Connection Ports</b>	VGA-In (15pin D-Sub) (x1), HDMI Number of Ports 1.4b (x1), Composite Video, Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RS-232, USB A (x1 (power 5V/1.5A)), USB miniB (Service)
General	<b>Lamp Life and Type</b>	5,000 / 7,000 / 10,000 Hours (Normal / Eco. / Long Eco. Mode), 203W
	<b>Speakers</b>	10W
	<b>Dimensions (W x D x H)</b>	313 x 236 x 114mm
	<b>Weight</b>	2.6 kg
	<b>Noise Level</b>	31dB / 27dB (Normal / Eco. Mode)
	<b>Power</b>	Supply: AC 100-240V, 50/60Hz Consumption: 210W (Eco. Mode), 250W (Normal Mode), <0.5W (Standby)
	<b>Warranty</b>	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whichever comes first, Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	<b>Standard Accessories</b>	Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	<b>Optional Accessories</b>	Spare Lamp P/N (XX5810005600 ), Remote Control P/N (SS-45-76U01G023-VV)
	<b>UPC Code</b>	813097023322