

VL-D210DL

14-in-1 DisplayLink USB-C Docking Station



Features

- ▶ Display Link compatible USB-C 3.2 Gen2 input including 96W device PD and 10Gbps transfer rate.
- ▶ Dual screen output MST mode (Windows and Mac)- 2x HDMI 2.0 output max 4K 60Hz or 2x DP1.2 single output max 4K 60Hz
- ▶ 3x USB 3.2 Gen1 5Gbps (Type A) ports, 4x USB 3.2 Gen2 10Gbps (2x Type A & 2x Type C) ports
- ▶ Gigabit ethernet for secure wired LAN access
- ▶ Support for peripheral device charging/powering. Compatible with USB 2.0, USB 3.2



Technical Data

VL-D210DL

Port type	Port type	Spec	Additional
Upstream Port	USB-C	DP1.4, USB 3.2 Gen2, PD3.0	Supports maximum 96W PD
Video Output Ports	HDMI 1 / DP1	Support maximum 4K@60Hz	Only one grouped port to be used at a time
	HDMI 2 / DP2	Support maximum 4K@60Hz	Only one grouped port to be used at a time
Down Stream Ports	3x USB-A	USB-A Gen1 - 5Gbps	Total current limit 1.8A
	1x USB-A	USB-A Gen2 - 10Gbps	Total current limit 1.8A
	USB-C	USB-C Gen2 - 10Gbps	Supports PD 20W charging
	USB-C	USB-C Gen2 - 10Gbps	Supports BC1.2, maximum 1.5-1.8A output
Other	RJ45	Supports 1G/100M/10M Ethernet	
	AUX 3.5mm headset		Supports both CTIA and OMPT pinning

General

Product Dimensions	190 x 88 x 37.5mm
Product Weight	602g
Housing Material	Plastic
Colour	Black
Operation Temperature	0°C to 40°C
Storage Temperature	-20°C to 45°C
Relative Humidity	20% to 85%
Power Supply	DC 20V 7.5A (US/EU standard, CE/FCC/UL certified)
Standby power consumption	< 2.5W
Power Consumption	System Max. 150W

Max output resolution	#	HDMI 1/DP 1 (1 of the 2)	HDMI 2/DP 2 (1 of the 2)
	1	3840 x 2160@60Hz	
	2		3840 x 2160@60Hz
	1	3840 x 2160@60Hz	3840 x 2160@60Hz

Set includes

Art.-No.	EAN
VL-D210DL	4251364737491

Contact

PureLink GmbH
Von-Liebig-Str. 10
48432 Rheine | Germany

☎ +49 5971 800 299-0
☎ +49 5971 800 299-99
✉ info@purelink.de



We regularly expand our product range. We will be happy to provide information on updates in this regard upon request.
All information is subject to confirmation and non-binding. Technical changes, printing errors and mistakes excepted.
The illustrations used in this document may differ from the delivered product.