



Product Specification

Product Type: LED All-in-one Display Terminal Product Model: XWALL- II 12020 Version: V1.8







Product Specification



Product Features

- Support video conference;
- Built-in 2*30W audio system;
- Built-in video processing function;
- Support frame rate conversion function;
- Support remote control via mobile devices;
- Support wireless Screen Sharing Function;
- Support Bluetooth 3.0 Function;
- Support various scene modes for different application scenarios;
- Support automatic brightness adjustment;
- ◆ Overall standby power consumption≤0.5W;
- Fully front access and hot swapping available;
- Support Wi-Fi dual frequency 2.4G/5G;
- Support adjustment modes via Wi-Fi, network cable and USB connection;
- Built-in Android 9.0 system and Apps;
- All-in-one ultra-slim and lightweight design,
- Built-in RS232 and RS485 interfaces can realize centralized control function
- Meet the RoHS directive requirements both in China and EU.







Product Parameter

| Size | 120 inch |
|------------------------------|---|
| Aspect Ratio | 16:9 |
| Resolution | 1280*720 |
| Overall Size (L*H) | 2678*1616mm |
| Display Area (L*H) | 2664*1499mm |
| Screen Thickness | 28.5mm |
| Net Weight | 90kg(wall-mounting bar and stand not included) |
| Recommended Viewing Distance | ≥4.2m |
| Maintenance Mode | Front Access |
| Installation Mode | Stand, Wall-mounting, Ceiling-hanging |
| Optical Parameter | |
| Brightness | 100-550cd/m²(Adjustable) |
| Refresh Rate | 1920/3840Hz |
| Gray Scale | 13-16bit |
| Contrast | 6500:1 |
| Color Temperature | 2300-9300K(Adjustable) |
| Viewing Angle | Horizontal 170°, Vertical 170° |
| LED Lifespan | ≥100,000hrs |
| Electrical Parameter | |
| Operation Voltage | 100-240VAC 50/60Hz |
| Standby Power | ≤0.5W |







| AveragePowerConsumptionofOverall Unit </th <th>0.60KW 1.5KW</th> | 0.60KW 1.5KW |
|--|--|
| System Parameter | |
| Operating System CPU | Android 9.0 Dual Cortex-A72 large core + four Cortex-A53 small core, frequency 2.0GHz |
| RAM | 4GB |
| Storage Media Format | 32GB Support mainstream video format such as MPEG1, MPEG2, MPEG4, WMV, MKV, TS, and flv; Support audio formats such as MP3; Support JPG, JPEG, BMP, PNG, GIF and other image format. |
| Environmental Parameter | |
| Operation Temperature | -10℃-40℃ |
| Operation Humidity | 10%-80%RH No condensation |







I/O Ports

| Туре | QTY | |
|-------------------------------------|----------------------------|--|
| HDMI 2.0 Input (do not support 4K) | 3 (2 internal, 1 external) | |
| HDMI 2.0 Output (do not support 4K) | 1 (internal) | |
| USB 2.0 | 1 (external) | |
| USB 3.0 | 1 (external) | |
| Туре С | 1 (external) | |
| 3.5 Audio Output | 2 (1 internal, 1 external) | |
| Audio Optical Output | 1 (internal) | |
| RS232 Port | 1 (internal) | |
| RS485 Port 1 (internal) | | |
| Bluetooth | 1 (wireless) | |
| LAN | 1 (internal) | |







Introduction to button and interface



| NO. | Description | | | |
|-----|---|--|--|--|
| 1 | Light Sensor | | | |
| 2 | IR | | | |
| 3 | Туре С | | | |
| 4 | USB3.0 | | | |
| 5 | USB2.0 | | | |
| 6 | Menu button(including brightness,color Temperature,contrast, sound,signal | | | |
| | source,test mode and Other sub-menus) | | | |
| 7 | Bright/OK (1.When the menu is Not called up,it is the brightness adjustment | | | |
| | button,and the + and - keys are used to adjust the brightness; 2.When the | | | |
| | menu is called up, it is used as confirm button.) | | | |
| 8 | 1.In the brightness adjustment mode, it is the brightness reduction key; | | | |
| | 2.When the Menu is called up,it is the Down/minus key | | | |
| 9 | 1.In the brightness adjustment mode, it is the brightness increase key; | | | |
| | 2.When the menu Is called up,it is the Up/Add key | | | |
| 10 | Standby/Wake up button | | | |
| 11 | Dual-color indicator light(red/blue) | | | |
| 12 | HDMI input (facedown) | | | |
| 13 | 3.5 Audio output port(facedown) | | | |







Introduction to remote control

| Button Icon | Introduction |
|-------------|-----------------------|
| Ċ | Standby/Wake up |
| | Up |
| | Down |
| | Confirm |
| | Left |
| | Right |
| + | Voice + |
| - | Voice - |
| 3 | Back |
| | Brightness Adjustment |
| Ξ | Channel Switch |
| (a) | Main Interface |









Accessories

| Remote Control | 1 | |
|----------------------------------|-----------------------------|---------------|
| Front Maintenance Tool | 1 | |
| Tool kit | 1 | |
| Wall-mounting Bar | 1 | |
| Hanging Structure | 1 set (optional) | |
| Stand | 1 set (optional) | |
| | | |
| Packing Dimension | | |
| Packing Dimension | Dimension | Quantity |
| | Dimension 1640*210*750mm | Quantity 2 |
| Item | | |
| Item Screen Packing Dimension | 1640*210*750mm | 2 |

Note:

• In case of special requirements, the packing quantity, weight and dimension may change, and the actual product received shall prevail.







Special Statement

◆ Intellectual Property Rights: The hardware design and software programs of this product are protected by copyright. The contents of this product and the manual shall not be copied without the authorization of the company.

- The contents of this manual are for reference only and do not constitute a commitment of any kind.
- The company reserves the right to make improvements and changes to the product design without prior notice

◆ Note: HDMI, HDMI HD Multimedia Interface and HDMI logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.

